



MATERIAL SAFETY DATA SHEET (MSDS)

1. PRODUCT & COMPANY IDENTIFICATION

Product identifier
Product Code 1404
Product Name FIXPROOF PU T

Intended use

Information about MSDS prepared company

INTERFIKS A.Ş. , Cavusbasi Cad. Yedekreis Sk. 7/2 Kavacık
Beykoz, Istanbul / TURKEY
Tel: +90(216) 425 1898 Faks: +90(216) 425 2099
E-posta: interfiks@interfiks.com.tr
[Internet: www.interfiks.com.tr](http://www.interfiks.com.tr)
[Responsible Person: sezin.selcuk@interfiks.com.tr](mailto:sezin.selcuk@interfiks.com.tr)

Emergency telephone number

+90 216 487 53 45

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical character Polyurethane

Hazardous ingredients

Xylene ≤ % 20 CAS NO:1330-20-7
R10
Xn; R20/21
Xi; R38

3. POTENTIAL HAZARDS

Hazards Information

Main Hazards

Causes skin irritation (Category 2) H315
Flammable liquid and vapour (Category 3) H226

4. FIRST AID MEASURES

Eye Contact

Rinse immediately for 15 minutes with plenty of water. Obtain medical attention.

Skin Contact

Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Inhalation

Remove to fresh air and keep at rest in a position comfortable for breathing.

Ingestion

Do not induce vomiting. Obtain emergency medical attention.

MATERIAL SAFETY DATA SHEET (MSDS)

5. FIRE FIGHTING MEASURES

Extinguishing media

Suitable Foam, water spray, dry powder, carbon dioxide, sand.

Not to be used Do not use a heavy water stream.

Combustion products Carbonmonoxide, carbondioxide

Other information Flammable liquid and vapour

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use suitable gas mask.No naked lights. No smoking. Use only outdoors or in a well-ventilated area.

Enviromental Precautions Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

7. HANDLING & STORAGE

Handling Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use explosion-proof electrical, ventilating, lighting, ..., equipment. Use only nonsparking tools.

Storage Keep container tightly closed. Ground/bond container and receiving equipment. Keep in fireproof place. Keep only in the original container in a cool, well ventilated place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Eye protection Chemical goggles or safety glasses

Hand protection PVC, neopren, nitrile or other type II gloves

Other Work clothes

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance Liquid

Colour Transparent

Odour Characteristic

pH Not determined.

Melting or freezing point Not determined.

Boiling point Not determined.

Distillation range Not determined.

Flash point 30 °C

Evaporation Rate Not determined.

MATERIAL SAFETY DATA SHEET (MSDS)

Lower inflammability limit	Flammable liquid and vapour
Upper inflammability limit	Not determined.
Lower explosive limit	Not determined.
Upper explosive limit	Not determined.
Density	1,00 ± 0,05 g/cm ³
Solubility	Water-insoluble
Auto-ignition temperature	Not determined.
Viscosity	650- 800 mPa
Flammability	Not determined.

10. STABILITY & REACTIVITY

Hazardous decomposition products	Not determined
Hazardous reactions	Not determined

11. INFORMATION ON TOXICITY

Information on toxicological effects

Skin irritation	may cause irritation
Eye irritation	may cause irritation
Other information	Toxic when inhale

12. INFORMATION ON ECOLOGICAL EFFECTS

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

13. DISPOSAL

Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Avoid release to the environment.

14. TRANSPORT

RID/ADR

UN N° : 1139

H.I. nr : 30

ADR - Class : 3

Labelling - Transport: 3

ADR-Classification code F1

ADR - Group III

ADR - Packing instructions P001 R001 LP001

ADR - Limited Quantity 5 L

MATERIAL SAFETY DATA SHEET (MSDS)

ICAO/IATA

UN N° 1139

IATA - Class or division 3
IATA - Packing group III
IATA - Passenger and
Cargo Aircraft Müsait
Passenger and Cargo -
Packing instruction 355
Passenger and Cargo -
Maximum
Quantity/Packing 60 L
IATA - Cargo only Müsait
Cargo only - Packing
instruction 366
Cargo only - Maximum
Quantity Packing 220 L
IATA - Limited
Quantites 10 L
ERG-Nr 3 L

Other information Not determined

15. REGULATIONS

Labelling Classified by EC directions/related laws

Symbol Xn: Harmful

R Phrase (R) R10 - Flammable.

S Phrase (S)
S 2 – Keep out of the reach of children
S 23 – Do not breathe vapour
S 26 – In case of contact with eyes, rinse immediately with
plenty of water and seek medical advice
S 40 – To clean the floor and all objects contaminated by this
material use xylene
S 46 - If swallowed, seek medical advice immediately and show
this container or label
S 51 - Use only in well-ventilated areas
S 24/25 - Avoid contact with skin and eyes

16. FURTHER INFORMATION

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness.

MATERIAL SAFETY DATA SHEET (MSDS)

The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.