

1. PRODUCT & COMPANY IDENTIFICATION

Product identifier

Product Code 1603

Product Name INTERPRIMER T-PU

Intended use

Information about MSDS prepared company

INTERFIKS A.Ş., Cavusbasi Cad. Yedekreis Sk. 7/2 Kavacık

Beykoz, Istanbul / TURKEY

Tel: +90(216) 425 1898 Faks: +90(216) 425 2099

E-posta: interfiks@interfiks.com.tr

Internet: www.interfiks.com.tr

Responsible Person: sezin.selcuk@interfiks.com.tr

Emergency telephone number

+90 216 487 53 45

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical character Polyurethane

Hazardous ingredients Xylene 40 - 45 % CAS NO: 1330-20-7

Propan-2-ol 40 - 45 % CAS NO: 67-63-0

F; R11

Xn; R20/21

R67

Xi; R36/38

3. POTENTIAL HAZARDS

Hazards Information Flammable liquid

Main Hazards Harmful if inhaled (Category 4) H332

Causes skin irritation (Category 2) H315 Causes serious eye irritation (Category 2) H319

4. FIRST AID MEASURES

Rinse immediately for 15 minutes with plenty of water. Obtain

medical attention.

Skin Contact Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower.

Remove to fresh air and keep at rest in a position comfortable

for breathing.

Ingestion Do not induce vomiting. Obtain emergency medical attention.

5. FIRE FIGHTING MEASURES

Extinguishing media

Suitable Foam, water spray, dry powder, carbon dioxide, sand.

Not to be used Do not use a heavy water stream.

Combustion products Carbonmonoxide, carbondioxide

Other information Flammable liquid and vapour

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use suitable gas mask.No naked lights. No smoking. Use only

outdoors or in a well-ventilated area.

Enviromental Prevent entry to sewers and public waters. Notify authorities if

Precautions product enters sewers or public waters.

7. HANDLING & STORAGE

Handling

Take precautionary measures against static discharge. Use only

outdoors or in a well-ventilated area. Use explosion-proof

electrical, ventilating, lighting, ..., equipment. Use only

nonsparking tools.

Keep container tightly closed. Ground/bond container and

Storage receiving equipment. Keep in fireproof place. Keep only in the

original container in a cool, well ventilated place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protective equipment

Respiratory protection In case of insufficient ventilation, wear suitable respiratory

equipment.

Eye protection Chemical goggles or safety glasses **Hand protection** PVC, neopren, nitrile or other type II gloves

Other Work clothes

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance Liquid
Colour Colourless
Odour Characteristic
pH Not determined.

Melting or freezing

Yayım Tarihi: 05.05.2014

Rev Tar / rev no: 000/00

point Not determined.

Boiling point Not determined.



Distillation range Not determined.

Flash point 20-24 °C

Evaporation Rate Not determined.

Lower inflammability

limit

Flammable

Upper inflammability

limit

Not determined.

Auto-ignition

temperature

Not determined.

Viscosity Not determined. Flammability Not determined.

10. STABILITY & REACTIVITY

Hazardous

decomposition Not determined

products

Hazardous reactions Not determined

11. INFORMATION ON TOXICITY

Information on toxicological effects

Skin irritation may cause irritation **Eye irritation** may cause irritation

Inhalation of cement dust may cause irritation of the

Other information respiratory tracts.

12. INFORMATION ON ECOLOGICAL EFFECTS

Prevent entry to sewers and public waters. Notify authorities if

product enters sewers or public waters.

13. DISPOSAL

Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Avoid

release to the environment.

14. TRANSPORT


RID/ADR

UN N°: 3082 H.I. nr: 90

ADR - Class: 9 Labelling - Transport: 9

ADR-Classification code M6

ADR - Group III





ADR - Packing P001 R001 LP001 instructions

ADR - Limited Quantity 5 L

ICAO/IATA

UN N° 3082

IATA - Class or division 9

IATA - Packing group III

IATA - Passenger and Cargo Aircraft Müsait

Passenger and Cargo - 964

Packing instruction

Passenger and Cargo -

Maximum 450L

Quantity/Packing

IATA - Cargo only Müsait

Cargo only - Packing 964

instruction

Cargo only - Maximum 450 L

Quantity Packing

IATA - Limited 30 kg G

Quantites

ERG-Nr 9 L

Not determined Other information

15. REGULATIONS

Labelling Classified by EC directions/related laws

Symbol Xn: Harmful

F: Highly Flammable

R Phrase (R) R 11 – Highly flammable

R 20/21 – Harmful by inhalation and in contact with skin

R 36/38 – Irritating to eyes and skin

R 67 – Vapours may cause drowsiness and dizziness

S Phrase (S) S 2 - Keep out of the reach of children

S 7 – Keep container tightly closed

S 16 - Keep away from sources of ignition - No smoking

S 25 - Avoid contact with eyes

S 26 – In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice

S 38 – In case of insufficient ventilation wear suitable

respiratory equipment



S 36/37 - Wear suitable protective clothing and gloves

16. FURTHER INFORMATION

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Yayım Tarihi: 05.05.2014 Rev Tar / rev no: 000/00

