

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Product name : FIXPROOF PU BITUMEN (A Component)  
Product code : 1301

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category : Professional use  
Use of the substance/mixture : Two Component, Bitumen-Reinforced And Polyurethane Based Liquid Waterproofing Compound

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

INTERFIKS YAPI KİMYASALLARI İNŞAAT SANAYİ VE TİCARET A.Ş.

Kavacık Mah. Yedek Reis Sok. No: 7 İç Kapı No: 2

Beykoz

İstanbul - TÜRKİYE

T +90(216) 425 18 98 - F +90(216) 425 20 99

[interfiks@interfiks.com.tr](mailto:interfiks@interfiks.com.tr) - [www.interfiks.com.tr](http://www.interfiks.com.tr)

**1.4. Emergency telephone number**

Emergency number : +90 216 487 53 45

Country	Official advisory body	Address	Emergency number	Comment
Turkey	Ulusal Zehir Merkezi (UZEM) Refik Saydam Hıfzıssıhha Merkezi Başkanlığı	Cemal Gürsel Cd. No: 18 Sıhhiye Çankaya 06590 Ankara	114	Information is provided to public and medical personnel on poisoning incidents via 114.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3 H226

Skin corrosion/irritation, Category 2 H315

Full text of H statements : see section 16

**Adverse physicochemical, human health and environmental effects**

Flammable liquid and vapour. Causes skin irritation.

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Warning

# FIXPROOF PU BITUMEN (A Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H315 - Causes skin irritation.
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P264 - Wash ... thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P321 - Specific treatment (see ... on this label).
Extra phrases	: For professional users only.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Xylene (Note C)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9	≤ 15.5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. People with over sensibility problems are not allowed to work or be exposed to the product. In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation.
-------------------------------------	---------------

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray, dry chemical powder, alcohol-resistant foam, carbon dioxide (CO <sub>2</sub> ).
Unsuitable extinguishing media	: Strong water jet.

# FIXPROOF PU BITUMEN (A Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour. Keep away from ignition sources (including static discharges). Contact with combustible material may cause fire.
- Reactivity in case of fire : At high temperature may liberate dangerous gases.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

- Precautionary measures fire : Approach from upwind. Use water spray or fog for cooling exposed containers. Keep away from combustible materials.
- Firefighting instructions : Use water spray or fog for cooling exposed containers. Cool adjacent tanks / containers / drums with water jet. Do not allow water to enter the vessels, a violent reaction may occur. Do not enter fire area without proper protective equipment, including respiratory protection. Exercise caution when fighting any chemical fire. Keep upwind. In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Other information : High temperature decomposition products are harmful by inhalation. Inhalation of vapour can cause breathing difficulties.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Access forbidden to unauthorised personnel. Use protective clothing. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters. Use care in walking on spilled material. Do not inhale vapour.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment. Dust formation: dust mask. Wear suitable protective clothing, gloves and eye or face protection.
- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not touch or walk on the spilled product. Evacuate unnecessary personnel. Mark out the contaminated area with signs and prevent access to unauthorized personnel.
- Measures in case of dust release : In case of dust production: protective goggles. Dust mask. In case of vapour formation use adequate respirator.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Only qualified personnel equipped with suitable protective equipment may intervene. Wear suitable protective clothing, gloves and eye/face protection.
- Emergency procedures : Avoid contact with skin and eyes. Do not touch spilled material. Evacuate unnecessary personnel. Keep away from combustible material. Keep public away from danger area. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ventilate area. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses. Do not discharge into drains or waterways without neutralizing.

### 6.3. Methods and material for containment and cleaning up

- For containment : Comply with the safety instructions. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Notify authorities if product enters sewers or public waters. Clean up any spills as soon as possible, using an absorbent material to collect it. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Sweep or shovel spills into appropriate container for disposal. Minimise generation of dust.
- Other information : Dispose of materials or solid residues at an authorized site. Dispose of contaminated materials in accordance with current regulations.

# FIXPROOF PU BITUMEN (A Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Use adequate ventilation to keep vapour concentrations below applicable standard. Take all necessary technical measures to avoid or minimize the release of the product on the workplace.
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid dust formation. Avoid prolonged and repeated contact with skin. Contaminated work clothing should not be allowed out of the workplace. Do not spray on an open flame or other ignition source. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Keep valves and fittings free from oil and grease. Take all necessary technical measures to avoid or minimize the release of the product on the workplace.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment. Comply with applicable regulations. Containers which are opened should be properly resealed and kept upright to prevent leakage. Ensure adequate ventilation, especially in confined areas.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Incompatible products	: Strong acids. Strong bases. Strong oxidizing agents. Peroxides. Explosives.
Incompatible materials	: Extremely high or low temperatures.
Maximum storage period	: 12 months
Storage temperature	: 5 – 25 °C
Heat and ignition sources	: Do not smoke. KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.
Information on mixed storage	: Keep away from food, drink and animal feeding stuffs.
Storage area	: Avoid : Extremely high or low temperatures. Heat and ignition sources.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Xylene (1330-20-7)	
EU - Occupational Exposure Limits	
Local name	Xylene, mixed isomers, pure
IOELV TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
IOELV TWA (ppm)	50 ppm
IOELV STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
IOELV STEL (ppm)	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Turkey - Occupational Exposure Limits	
Local name	Ksilen

# FIXPROOF PU BITUMEN (A Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

### Xylene (1330-20-7)

OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup> (karışım izomerleri, saf)
OEL TWA (ppm)	50 ppm (karışım izomerleri, saf)
OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup> (karışım izomerleri, saf)
OEL STEL (ppm)	100 ppm (karışım izomerleri, saf)
Comments	Deri
Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing. Carry out operations in the open/under local exhaust/ventilation or with respiratory protection. Consider the use of a work permit system e.g. for maintenance activities. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. In the event that dust and/or fine particles are generated with this product, it is prudent to minimize prolonged inhalation exposure to these forms not to exceed the occupational exposure limit. Measure concentrations regularly, and at the time of any change occurring in conditions likely to have consequences on workers exposure.

#### Personal protective equipment:

Safety glasses. Gloves.

#### Hand protection:

Protective gloves. EN 374

#### Eye protection:

Safety glasses. EN 166. Where excessive dust may result, wear goggles

#### Skin and body protection:

Wear suitable protective clothing. In case of dust production: dustproof clothing. In case of dust production: head/neck protection. Where contact with eyes or skin is likely, wear suitable protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Dust production: dust mask with filter type P1. Where excessive vapour may result, wear approved mask

#### Personal protective equipment symbol(s):



#### Environmental exposure controls:

Avoid release to the environment.

#### Consumer exposure controls:

Do not eat, drink or smoke during use. Always wash hands after handling the product. Avoid contact with skin and eyes. Avoid contact during pregnancy/while nursing.

#### Other information:

Always wash hands after handling the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

# FIXPROOF PU BITUMEN (A Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

Appearance	: Clear.
Colour	: Clear.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 42 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1 g/cm <sup>3</sup> ± 0,05
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 1000 – 1500 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Peroxides. Explosives.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified

# FIXPROOF PU BITUMEN (A Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

### Xylene (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified  
Not rapidly degradable

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations. Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015. Regulation on Incineration of Waste Materials published in the Official Journal numbered 27721 on October 6, 2010.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions. Do not remove as household garbage.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Flammable vapours may accumulate in the container. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.






# FIXPROOF PU BITUMEN (A Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

### SECTION 14: Transport information


In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 1139	UN 1139	UN 1139	UN 1139	UN 1139
<b>14.2. UN proper shipping name</b>				
COATING SOLUTION (Xylene)	COATING SOLUTION (Xylene)	Coating solution (Xylene)	COATING SOLUTION (Xylene)	COATING SOLUTION (Xylene)
<b>Transport document description</b>				
UN 1139 COATING SOLUTION (Xylene), 3, III, (D/E)	UN 1139 COATING SOLUTION (Xylene), 3, III	UN 1139 Coating solution (Xylene), 3, III	UN 1139 COATING SOLUTION (Xylene), 3, III	UN 1139 COATING SOLUTION (Xylene), 3, III
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

#### Transport by sea

Special provisions (IMDG)	: 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1



# FIXPROOF PU BITUMEN (A Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

### Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: F1
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

##### Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG) Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)
-------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

# FIXPROOF PU BITUMEN (A Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)  
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed  
SZW-lijst van mutagene stoffen : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Xylene is listed

### Denmark

Class for fire hazard : Class II-1  
Store unit : 5 liter  
Classification remarks : R10 <H226;H315>; Emergency management guidelines for the storage of flammable liquids must be followed

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative

# FIXPROOF PU BITUMEN (A Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

CAS-No.	Chemical Abstract Service number
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS	Chemical Abstracts Service (division of the American Chemical Society)
EC-No.	European Community number
EN	European Standard
IOELV	Indicative Occupational Exposure Limit Value
N.O.S.	Not Otherwise Specified
OEL	Occupational Exposure Limit
Pow (log)	n-octanol/water partition coefficient
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
ThOD	Theoretical oxygen demand (ThOD)
TRGS	Technical Rules for Hazardous Substances
VOC	Volatile Organic Compounds
WGK	Water Hazard Class

Data sources : Classification according to Regulation (EC) No. 1272/2008 [CLP]. ECHA (European Chemicals Agency). Supplier's safety documents.

### Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Flam. Liq. 3	H226
Skin Irrit. 2	H315

### Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.

SDS EU (REACH Annex II)

**DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Product name : FIXPROOF PU BITUMEN (B Component)  
Product code : 1301

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category : Professional use  
Use of the substance/mixture : Two Component, Bitumen-Reinforced And Polyurethane Based Liquid Waterproofing Compound

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

INTERFIKS YAPI KİMYASALLARI İNŞAAT SANAYİ VE TİCARET A.Ş.

Kavacık Mah. Yedek Reis Sok. No: 7 İç Kapı No: 2

Beykoz

İstanbul - TÜRKİYE

T +90(216) 425 18 98 - F +90(216) 425 20 99

[interfiks@interfiks.com.tr](mailto:interfiks@interfiks.com.tr) - [www.interfiks.com.tr](http://www.interfiks.com.tr)

**1.4. Emergency telephone number**

Emergency number : +90 216 487 53 45

Country	Official advisory body	Address	Emergency number	Comment
Turkey	Ulusal Zehir Merkezi (UZEM) Refik Saydam Hıfzıssıhha Merkezi Başkanlığı	Cemal Gürsel Cd. No: 18 Sıhhiye Çankaya 06590 Ankara	114	Information is provided to public and medical personnel on poisoning incidents via 114.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2 H225

Skin corrosion/irritation, Category 2 H315

Full text of H statements : see section 16

**Adverse physicochemical, human health and environmental effects**

Highly flammable liquid and vapour. Causes skin irritation.

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

# FIXPROOF PU BITUMEN (B Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H315 - Causes skin irritation.
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P264 - Wash ... thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P321 - Specific treatment (see ... on this label).

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Xylene (Note C)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9	≤ 14	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. People with over sensibility problems are not allowed to work or be exposed to the product. In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation.
-------------------------------------	---------------

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray, dry chemical powder, alcohol-resistant foam, carbon dioxide (CO <sub>2</sub> ).
Unsuitable extinguishing media	: Strong water jet.

# FIXPROOF PU BITUMEN (B Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour. Keep away from ignition sources (including static discharges). Contact with combustible material may cause fire.
- Reactivity in case of fire : At high temperature may liberate dangerous gases.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

- Precautionary measures fire : Approach from upwind. Use water spray or fog for cooling exposed containers. Keep away from combustible materials.
- Firefighting instructions : Use water spray or fog for cooling exposed containers. Cool adjacent tanks / containers / drums with water jet. Do not allow water to enter the vessels, a violent reaction may occur. Do not enter fire area without proper protective equipment, including respiratory protection. Exercise caution when fighting any chemical fire. Keep upwind. In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Other information : High temperature decomposition products are harmful by inhalation. Inhalation of vapour can cause breathing difficulties.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Access forbidden to unauthorised personnel. Use protective clothing. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters. Use care in walking on spilled material. Do not inhale vapour.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment. Dust formation: dust mask. Wear suitable protective clothing, gloves and eye or face protection.
- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not touch or walk on the spilled product. Evacuate unnecessary personnel. Mark out the contaminated area with signs and prevent access to unauthorized personnel.
- Measures in case of dust release : In case of dust production: protective goggles. Dust mask. In case of vapour formation use adequate respirator.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Only qualified personnel equipped with suitable protective equipment may intervene. Wear suitable protective clothing, gloves and eye/face protection.
- Emergency procedures : Avoid contact with skin and eyes. Do not touch spilled material. Evacuate unnecessary personnel. Keep away from combustible material. Keep public away from danger area. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ventilate area. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses. Do not discharge into drains or waterways without neutralizing.

### 6.3. Methods and material for containment and cleaning up

- For containment : Comply with the safety instructions. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Notify authorities if product enters sewers or public waters. Clean up any spills as soon as possible, using an absorbent material to collect it. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Sweep or shovel spills into appropriate container for disposal. Minimise generation of dust.
- Other information : Dispose of materials or solid residues at an authorized site. Dispose of contaminated materials in accordance with current regulations.

# FIXPROOF PU BITUMEN (B Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

### 6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Use adequate ventilation to keep vapour concentrations below applicable standard. Take all necessary technical measures to avoid or minimize the release of the product on the workplace.
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid dust formation. Avoid prolonged and repeated contact with skin. Contaminated work clothing should not be allowed out of the workplace. Do not spray on an open flame or other ignition source. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Keep valves and fittings free from oil and grease. Take all necessary technical measures to avoid or minimize the release of the product on the workplace.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment. Comply with applicable regulations. Containers which are opened should be properly resealed and kept upright to prevent leakage. Ensure adequate ventilation, especially in confined areas.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Incompatible products	: Strong acids. Strong bases. Strong oxidizing agents. Peroxides. Explosives.
Incompatible materials	: Extremely high or low temperatures.
Maximum storage period	: 12 months
Storage temperature	: 5 – 25 °C
Heat and ignition sources	: Do not smoke. KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.
Information on mixed storage	: Keep away from food, drink and animal feeding stuffs.
Storage area	: Avoid : Extremely high or low temperatures. Heat and ignition sources.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Xylene (1330-20-7)	
EU - Occupational Exposure Limits	
Local name	Xylene, mixed isomers, pure
IOELV TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
IOELV TWA (ppm)	50 ppm
IOELV STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup>
IOELV STEL (ppm)	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Turkey - Occupational Exposure Limits	
Local name	Ksilen

# FIXPROOF PU BITUMEN (B Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

### Xylene (1330-20-7)

OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup> (karışım izomerleri, saf)
OEL TWA (ppm)	50 ppm (karışım izomerleri, saf)
OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup> (karışım izomerleri, saf)
OEL STEL (ppm)	100 ppm (karışım izomerleri, saf)
Comments	Deri
Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing. Carry out operations in the open/under local exhaust/ventilation or with respiratory protection. Consider the use of a work permit system e.g. for maintenance activities. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. In the event that dust and/or fine particles are generated with this product, it is prudent to minimize prolonged inhalation exposure to these forms not to exceed the occupational exposure limit. Measure concentrations regularly, and at the time of any change occurring in conditions likely to have consequences on workers exposure.

#### Personal protective equipment:

Safety glasses. Gloves.

#### Hand protection:

Protective gloves. EN 374

#### Eye protection:

Safety glasses. EN 166. Where excessive dust may result, wear goggles

#### Skin and body protection:

Wear suitable protective clothing. In case of dust production: dustproof clothing. In case of dust production: head/neck protection. Where contact with eyes or skin is likely, wear suitable protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Dust production: dust mask with filter type P1. Where excessive vapour may result, wear approved mask

#### Personal protective equipment symbol(s):



#### Environmental exposure controls:

Avoid release to the environment.

#### Consumer exposure controls:

Do not eat, drink or smoke during use. Always wash hands after handling the product. Avoid contact with skin and eyes. Avoid contact during pregnancy/while nursing.

#### Other information:

Always wash hands after handling the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid



# FIXPROOF PU BITUMEN (B Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

Appearance	: Viscous liquid.
Colour	: Black.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 144.4 °C Xylene
Flash point	: 21 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.95 g/cm <sup>3</sup> ± 0,05
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 1000 – 1500 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Peroxides. Explosives.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified

# FIXPROOF PU BITUMEN (B Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

### Xylene (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified  
Not rapidly degradable

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations. Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015. Regulation on Incineration of Waste Materials published in the Official Journal numbered 27721 on October 6, 2010.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions. Do not remove as household garbage.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Flammable vapours may accumulate in the container. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.






# FIXPROOF PU BITUMEN (B Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

### SECTION 14: Transport information


In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 1139	UN 1139	UN 1139	UN 1139	UN 1139
<b>14.2. UN proper shipping name</b>				
COATING SOLUTION (Xylene)	COATING SOLUTION (Xylene)	Coating solution (Xylene)	COATING SOLUTION (Xylene)	COATING SOLUTION (Xylene)
<b>Transport document description</b>				
UN 1139 COATING SOLUTION (Xylene), 3, II, (D/E)	UN 1139 COATING SOLUTION (Xylene), 3, II	UN 1139 Coating solution (Xylene), 3, II	UN 1139 COATING SOLUTION (Xylene), 3, II	UN 1139 COATING SOLUTION (Xylene), 3, II
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
II	II	II	II	II
<b>14.5. Environmental hazards</b>				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : F1  
 Special provisions (ADR) : 640C  
 Limited quantities (ADR) : 5I  
 Excepted quantities (ADR) : E2  
 Packing instructions (ADR) : P001  
 Mixed packing provisions (ADR) : MP19  
 Portable tank and bulk container instructions (ADR) : T4  
 Portable tank and bulk container special provisions (ADR) : TP1, TP8  
 Tank code (ADR) : L1.5BN  
 Vehicle for tank carriage : FL  
 Transport category (ADR) : 2  
 Special provisions for carriage - Operation (ADR) : S2, S20  
 Hazard identification number (Kemler No.) : 33  
 Orange plates :



Tunnel restriction code (ADR) : D/E  
 EAC code : •3YE

#### Transport by sea

Limited quantities (IMDG) : 5 L  
 Excepted quantities (IMDG) : E2  
 Packing instructions (IMDG) : P001

# FIXPROOF PU BITUMEN (B Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

### Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

### Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 640C
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

### Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 640C
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP8
Tank codes for RID tanks (RID)	: L1.5BN
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

##### Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG) Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)
-------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

# FIXPROOF PU BITUMEN (B Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)  
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed  
SZW-lijst van mutagene stoffen : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed  
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Xylene is listed

### Denmark

Class for fire hazard : Class I-1  
Store unit : 1 liter  
Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative

# FIXPROOF PU BITUMEN (B Component)

## Safety Data Sheet

according to Regulation (EU) 2015/830

CAS-No.	Chemical Abstract Service number
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS	Chemical Abstracts Service (division of the American Chemical Society)
EC-No.	European Community number
EN	European Standard
IOELV	Indicative Occupational Exposure Limit Value
N.O.S.	Not Otherwise Specified
OEL	Occupational Exposure Limit
Pow (log)	n-octanol/water partition coefficient
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
ThOD	Theoretical oxygen demand (ThOD)
TRGS	Technical Rules for Hazardous Substances
VOC	Volatile Organic Compounds
WGK	Water Hazard Class

Data sources : Classification according to Regulation (EC) No. 1272/2008 [CLP]. ECHA (European Chemicals Agency). Supplier's safety documents.

### Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Flam. Liq. 2	H225
Skin Irrit. 2	H315

### Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.

SDS EU (REACH Annex II)

**DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable