



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : INTERFLEX EPO AD (A Component)
Product code : 7302
Type of product : Adhesives

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Two Component, Epoxy Based Expansion Band Adhesive

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

INTERFIKS YAPI KİMYASALLARI İNŞAAT SANAYİ VE TİCARET A.Ş.

Kavacık Mah. Yedek Reis Sok. No: 7 İç Kapı No: 2

Beykoz

İstanbul - TÜRKİYE

T +90(216) 425 18 98 - F +90(216) 425 20 99

interfiks@interfiks.com.tr - www.interfiks.com.tr

1.4. Emergency telephone number

Emergency number : +90 216 487 53 45

Country	Official advisory body	Address	Emergency number	Comment
Turkey	Ulusal Zehir Merkezi (UZEM) Refik Saydam Hıfzıssıhha Merkezi Başkanlığı	Cemal Gürsel Cd. No: 18 Sıhhiye Çankaya 06590 Ankara	114	Information is provided to public and medical personnel on poisoning incidents via 114.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Causes skin irritation. Causes serious eye irritation. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



INTERFLEX EPO AD (A Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

	GHS07	GHS09
Signal word (CLP)	: Warning	
Hazardous ingredients	: reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	
Hazard statements (CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H411 - Toxic to aquatic life with long lasting effects.	
Precautionary statements (CLP)	: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash ... thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P321 - Specific treatment (see ... on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P391 - Collect spillage.	

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8	< 40	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Specific concentration limits:

Name	Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8	(5 \leq C < 100) Eye Irrit. 2, H319 (5 \leq C < 100) Skin Irrit. 2, H315

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. People with over sensibility problems are not allowed to work or be exposed to the product. In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

INTERFLEX EPO AD (A Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray, dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).
Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Keep away from ignition sources (including static discharges). Contact with combustible material may cause fire.
Reactivity in case of fire : At high temperature may liberate dangerous gases.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire : Approach from upwind. Use water spray or fog for cooling exposed containers. Keep away from combustible materials.
Firefighting instructions : Use water spray or fog for cooling exposed containers. Cool adjacent tanks / containers / drums with water jet. Do not allow water to enter the vessels, a violent reaction may occur. Do not enter fire area without proper protective equipment, including respiratory protection. Exercise caution when fighting any chemical fire. Keep upwind. In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : High temperature decomposition products are harmful by inhalation. Inhalation of vapour can cause breathing difficulties.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Access forbidden to unauthorised personnel. Use protective clothing. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters. Use care in walking on spilled material. Do not inhale vapour.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment. Dust formation: dust mask. Wear suitable protective clothing, gloves and eye or face protection.
Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not touch or walk on the spilled product. Evacuate unnecessary personnel. Mark out the contaminated area with signs and prevent access to unauthorized personnel. Avoid breathing dust/fume/gas/mist/vapours/spray.
Measures in case of dust release : In case of dust production: protective goggles. Dust mask. In case of vapour formation use adequate respirator.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Only qualified personnel equipped with suitable protective equipment may intervene. Wear suitable protective clothing, gloves and eye/face protection.
Emergency procedures : Avoid contact with skin and eyes. Do not touch spilled material. Evacuate unnecessary personnel. Keep away from combustible material. Keep public away from danger area. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses. Do not discharge into drains or waterways without neutralizing.

INTERFLEX EPO AD (A Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage. Comply with the safety instructions. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Mechanically recover the product. Clean up any spills as soon as possible, using an absorbent material to collect it. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Sweep or shovel spills into appropriate container for disposal. Minimise generation of dust.
- Other information : Dispose of materials or solid residues at an authorized site. Dispose of contaminated materials in accordance with current regulations.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Use adequate ventilation to keep vapour concentrations below applicable standard. Take all necessary technical measures to avoid or minimize the release of the product on the workplace.
- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid dust formation. Avoid prolonged and repeated contact with skin. Contaminated work clothing should not be allowed out of the workplace. Do not spray on an open flame or other ignition source. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Keep valves and fittings free from oil and grease. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray.
- Handling temperature : 5 – 30 °C
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations. Containers which are opened should be properly resealed and kept upright to prevent leakage. Ensure adequate ventilation, especially in confined areas.
- Storage conditions : Store in a well-ventilated place. Keep cool.
- Incompatible products : Strong acids. Strong bases. Strong oxidizing agents. Peroxides. Explosives.
- Incompatible materials : Extremely high or low temperatures.
- Maximum storage period : 12 months
- Storage temperature : ≤ 4 °C
- Heat and ignition sources : Do not smoke. KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.
- Information on mixed storage : Keep away from food, drink and animal feeding stuffs.
- Storage area : Avoid : Extremely high or low temperatures. Heat and ignition sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

INTERFLEX EPO AD (A Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing. Carry out operations in the open/under local exhaust/ventilation or with respiratory protection. Consider the use of a work permit system e.g. for maintenance activities. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. In the event that dust and/or fine particles are generated with this product, it is prudent to minimize prolonged inhalation exposure to these forms not to exceed the occupational exposure limit. Measure concentrations regularly, and at the time of any change occurring in conditions likely to have consequences on workers exposure.

Personal protective equipment:

Safety glasses. Gloves. Dust formation: dust mask.

Hand protection:

Protective gloves. EN 374

Eye protection:

Safety glasses. EN 166. Where excessive dust may result, wear goggles

Skin and body protection:

Wear suitable protective clothing. In case of dust production: dustproof clothing. In case of dust production: head/neck protection. Where contact with eyes or skin is likely, wear suitable protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Dust production: dust mask with filter type P1. Where excessive vapour may result, wear approved mask

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Do not eat, drink or smoke during use. Always wash hands after handling the product. Avoid contact with skin and eyes. Avoid contact during pregnancy/while nursing.

Other information:

Always wash hands after handling the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Paste.
Colour	: Cream.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available

INTERFLEX EPO AD (A Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.9 g/cm ³ ± 0,05
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Peroxides. Explosives.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

LD50 oral rat	> 2000 mg/kg (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

INTERFLEX EPO AD (A Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
Not rapidly degradable	

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

LC50 fish 2	2.3 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Semi-static system; Fresh water; Experimental value)
-------------	--

12.2. Persistence and degradability

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

Persistence and degradability	Not readily biodegradable in water. Hydrolysis in water. Low potential for adsorption in soil.
-------------------------------	--

12.3. Bioaccumulative potential

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

BCF other aquatic organisms 1	3-31,BCF
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)

Surface tension	0.0587-0.0589,20 °C
Partition coefficient n-octanol/water (Log Koc)	Koc, SRC PCKOCWIN v2.0; 445; QSAR; log Koc; SRC PCKOCWIN v2.0; 2.65; QSAR

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations. Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015. Regulation on Incineration of Waste Materials published in the Official Journal numbered 27721 on October 6, 2010.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions. Do not remove as household garbage.
Sewage disposal recommendations	: Disposal must be done according to official regulations.

INTERFLEX EPO AD (A Component)

Safety Data Sheet






according to Regulation (EU) 2015/830

Additional information

: Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 3077	UN 3077	UN 3077	UN 3077	UN 3077
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))	Environmentally hazardous substance, solid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))
Transport document description				
UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III, (-)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III, MARINE POLLUTANT	UN 3077 Environmentally hazardous substance, solid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M7
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5kg
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P002, IBC08, LP02, R001
Special packing provisions (ADR)	: PP12, B3
Mixed packing provisions (ADR)	: MP10

INTERFLEX EPO AD (A Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

Portable tank and bulk container instructions (ADR) : T1, BK1, BK2, BK3

Portable tank and bulk container special provisions : TP33

(ADR)

Tank code (ADR) : SGAV, LGBV

Vehicle for tank carriage : AT

Transport category (ADR) : 3

Special provisions for carriage - Packages (ADR) : V13


Special provisions for carriage - Bulk (ADR) : VC1, VC2

Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates :



Tunnel restriction code (ADR) : -

EAC code : 2Z

Transport by sea

Special provisions (IMDG) : 274, 335, 966, 967, 969

Limited quantities (IMDG) : 5 kg

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : LP02, P002

Special packing provisions (IMDG) : PP12

IBC packing instructions (IMDG) : IBC08

IBC special provisions (IMDG) : B3

Tank instructions (IMDG) : BK1, BK2, BK3, T1

Tank special provisions (IMDG) : TP33

EmS-No. (Fire) : F-A

EmS-No. (Spillage) : S-F

Stowage category (IMDG) : A

Stowage and handling (IMDG) : SW23

Air transport

PCA Excepted quantities (IATA) : E1

PCA Limited quantities (IATA) : Y956

PCA limited quantity max net quantity (IATA) : 30kgG

PCA packing instructions (IATA) : 956

PCA max net quantity (IATA) : 400kg

CAO packing instructions (IATA) : 956

CAO max net quantity (IATA) : 400kg

Special provisions (IATA) : A97, A158, A179, A197

ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M7

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 kg

Excepted quantities (ADN) : E1

Equipment required (ADN) : PP, A

Number of blue cones/lights (ADN) : 0

Additional requirements/Remarks (ADN) : * Only in the molten state. ** For carriage in bulk see also 7.1.4.1. *** Only in the case of transport in bulk.

Rail transport

Classification code (RID) : M7

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5kg

Excepted quantities (RID) : E1

Packing instructions (RID) : P002, IBC08, LP02, R001

Special packing provisions (RID) : PP12, B3

Mixed packing provisions (RID) : MP10

Portable tank and bulk container instructions (RID) : T1, BK1, BK2, BK3

Portable tank and bulk container special provisions : TP33

(RID)

Tank codes for RID tanks (RID) : SGAV, LGBV

INTERFLEX EPO AD (A Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W13
Special provisions for carriage – Bulk (RID)	: VC1, VC2
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW31
Colis express (express parcels) (RID)	: CE11
Hazard identification number (RID)	: 90

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration

INTERFLEX EPO AD (A Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
CAS-No.	Chemical Abstract Service number
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS	Chemical Abstracts Service (division of the American Chemical Society)
EC-No.	European Community number
EN	European Standard
IOELV	Indicative Occupational Exposure Limit Value
N.O.S.	Not Otherwise Specified
OEL	Occupational Exposure Limit
Pow (log)	n-octanol/water partition coefficient
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
ThOD	Theoretical oxygen demand (ThOD)
TRGS	Technical Rules for Hazardous Substances
VOC	Volatile Organic Compounds
WGK	Water Hazard Class

Data sources : Classification according to Regulation (EC) No. 1272/2008 [CLP]. ECHA (European Chemicals Agency). Supplier's safety documents.

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

INTERFLEX EPO AD (A Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : INTERFLEX EPO AD (B Component)
Product code : 7302
Type of product : Adhesives

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Two Component, Epoxy Based Expansion Band Adhesive

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

INTERFIKS YAPI KİMYASALLARI İNŞAAT SANAYİ VE TİCARET A.Ş.

Kavacık Mah. Yedek Reis Sok. No: 7 İç Kapı No: 2

Beykoz

İstanbul - TÜRKİYE

T +90(216) 425 18 98 - F +90(216) 425 20 99

interfiks@interfiks.com.tr - www.interfiks.com.tr

1.4. Emergency telephone number

Emergency number : +90 216 487 53 45

Country	Official advisory body	Address	Emergency number	Comment
Turkey	Ulusal Zehir Merkezi (UZEM) Refik Saydam Hıfzıssıhha Merkezi Başkanlığı	Cemal Gürsel Cd. No: 18 Sıhhiye Çankaya 06590 Ankara	114	Information is provided to public and medical personnel on poisoning incidents via 114.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315

Serious eye damage/eye irritation, Category 2 H319

Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

INTERFLEX EPO AD (B Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

Signal word (CLP)	: Warning
Hazardous ingredients	: 3-aminomethyl-3,5,5-trimethylcyclohexylamine; m-phenylenebis(methylamine)
Hazard statements (CLP)	: H315 - Causes skin irritation. H319 - Causes serious eye irritation. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P264 - Wash ... thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P321 - Specific treatment (see ... on this label). P337+P313 - If eye irritation persists: Get medical advice/attention.
EUH-statements	: EUH208 - Contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine). May produce an allergic reaction.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl alcohol	(CAS-No.) 100-51-6 (EC-No.) 202-859-9 (EC Index-No.) 603-057-00-5	≤ 100	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Oral), H302
3-aminomethyl-3,5,5-trimethylcyclohexylamine	(CAS-No.) 2855-13-2 (EC-No.) 220-666-8 (EC Index-No.) 612-067-00-9	≤ 100	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
m-phenylenebis(methylamine)	(CAS-No.) 1477-55-0 (EC-No.) 216-032-5	≤ 100	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Skin Sens. 1B, H317 Aquatic Chronic 3, H412

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. People with over sensibility problems are not allowed to work or be exposed to the product. In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

INTERFLEX EPO AD (B Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray, dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).
Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Keep away from ignition sources (including static discharges). Contact with combustible material may cause fire.
Reactivity in case of fire : At high temperature may liberate dangerous gases.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire : Approach from upwind. Use water spray or fog for cooling exposed containers. Keep away from combustible materials.
Firefighting instructions : Use water spray or fog for cooling exposed containers. Cool adjacent tanks / containers / drums with water jet. Do not allow water to enter the vessels, a violent reaction may occur. Do not enter fire area without proper protective equipment, including respiratory protection. Exercise caution when fighting any chemical fire. Keep upwind. In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : High temperature decomposition products are harmful by inhalation. Inhalation of vapour can cause breathing difficulties.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Access forbidden to unauthorised personnel. Use protective clothing. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters. Use care in walking on spilled material. Do not inhale vapour.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment. Dust formation: dust mask. Wear suitable protective clothing, gloves and eye or face protection.
Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not touch or walk on the spilled product. Evacuate unnecessary personnel. Mark out the contaminated area with signs and prevent access to unauthorized personnel.
Measures in case of dust release : In case of dust production: protective goggles. Dust mask. In case of vapour formation use adequate respirator.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Only qualified personnel equipped with suitable protective equipment may intervene. Wear suitable protective clothing, gloves and eye/face protection.
Emergency procedures : Avoid contact with skin and eyes. Do not touch spilled material. Evacuate unnecessary personnel. Keep away from combustible material. Keep public away from danger area. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses. Do not discharge into drains or waterways without neutralizing.

INTERFLEX EPO AD (B Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

- For containment : Comply with the safety instructions. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Mechanically recover the product. Clean up any spills as soon as possible, using an absorbent material to collect it. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Sweep or shovel spills into appropriate container for disposal. Minimise generation of dust.
- Other information : Dispose of materials or solid residues at an authorized site. Dispose of contaminated materials in accordance with current regulations.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Use adequate ventilation to keep vapour concentrations below applicable standard. Take all necessary technical measures to avoid or minimize the release of the product on the workplace.
- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid dust formation. Avoid prolonged and repeated contact with skin. Contaminated work clothing should not be allowed out of the workplace. Do not spray on an open flame or other ignition source. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Keep valves and fittings free from oil and grease. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Take precautionary measures against static discharge.
- Handling temperature : 5 – 30 °C
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations. Containers which are opened should be properly resealed and kept upright to prevent leakage. Ensure adequate ventilation, especially in confined areas.
- Storage conditions : Store in a well-ventilated place. Keep cool.
- Incompatible products : Strong acids. Strong bases. Strong oxidizing agents. Peroxides. Explosives.
- Incompatible materials : Extremely high or low temperatures.
- Maximum storage period : 12 months
- Storage temperature : ≤ 4 °C
- Heat and ignition sources : Do not smoke. KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.
- Information on mixed storage : Keep away from food, drink and animal feeding stuffs.
- Storage area : Avoid : Extremely high or low temperatures. Heat and ignition sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

benzyl alcohol (100-51-6)

Germany - Occupational Exposure Limits (TRGS 900)

TRGS 900 Local name	Benzylalkohol
Occupational exposure limit value (mg/m ³)	22 mg/m ³
Occupational exposure limit value (ppm)	5 ppm

INTERFLEX EPO AD (B Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

benzyl alcohol (100-51-6)

Limitation of exposure peaks	2(l)
TRGS 900 Remark	DFG;H;Y;11
TRGS 900 Regulatory reference	TRGS900

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing. Carry out operations in the open/under local exhaust/ventilation or with respiratory protection. Consider the use of a work permit system e.g. for maintenance activities. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. In the event that dust and/or fine particles are generated with this product, it is prudent to minimize prolonged inhalation exposure to these forms not to exceed the occupational exposure limit. Measure concentrations regularly, and at the time of any change occurring in conditions likely to have consequences on workers exposure.

Personal protective equipment:

Safety glasses. Gloves. Dust formation: dust mask.

Hand protection:

Protective gloves. EN 374

Eye protection:

Safety glasses. EN 166. Where excessive dust may result, wear goggles

Skin and body protection:

Wear suitable protective clothing. In case of dust production: dustproof clothing. In case of dust production: head/neck protection. Where contact with eyes or skin is likely, wear suitable protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Dust production: dust mask with filter type P1. Where excessive vapour may result, wear approved mask

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Do not eat, drink or smoke during use. Always wash hands after handling the product. Avoid contact with skin and eyes. Avoid contact during pregnancy/while nursing.

Other information:

Always wash hands after handling the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Paste.
Colour	: Black.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available

INTERFLEX EPO AD (B Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.9 g/cm ³ ± 0,05
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Peroxides. Explosives.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

benzyl alcohol (100-51-6)

LD50 oral	1620 mg/kg bodyweight
LD50 dermal	2500 mg/kg bodyweight
LC50 inhalation rat (mg/l)	4.178 mg/l/4h (OECD 403)

INTERFLEX EPO AD (B Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

LD50 oral rat	1030 mg/kg
---------------	------------

m-phenylenebis(methylamine) (1477-55-0)

LD50 oral rat	940 mg/kg
LD50 dermal rat	> 3100 mg/kg bodyweight Animal: rat
LC50 inhalation rat (mg/l)	2.4 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
Not rapidly degradable	

m-phenylenebis(methylamine) (1477-55-0)

LC50 fish 1	87.6 mg/l Test organisms (species): Oryzias latipes
EC50 Daphnia 1	15.2 mg/l Test organisms (species): Daphnia magna
EC50 72h algae (1)	20.3 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h algae (2)	33.3 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	15 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	4.7 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

INTERFLEX EPO AD (B Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Regional legislation (waste) : Disposal must be done according to official regulations. Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015. Regulation on Incineration of Waste Materials published in the Official Journal numbered 27721 on October 6, 2010.
- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions. Do not remove as household garbage.
- Sewage disposal recommendations : Disposal must be done according to official regulations.
- Additional information : Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

INTERFLEX EPO AD (B Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

giftige stoffen – Borstvoeding

NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

giftige stoffen – Vruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

giftige stoffen – Ontwikkeling

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

INTERFLEX EPO AD (B Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
CAS-No.	Chemical Abstract Service number
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS	Chemical Abstracts Service (division of the American Chemical Society)
EC-No.	European Community number
EN	European Standard
IOELV	Indicative Occupational Exposure Limit Value
N.O.S.	Not Otherwise Specified
OEL	Occupational Exposure Limit
Pow (log)	n-octanol/water partition coefficient
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
ThOD	Theoretical oxygen demand (ThOD)
TRGS	Technical Rules for Hazardous Substances
VOC	Volatile Organic Compounds
WGK	Water Hazard Class

Data sources : Classification according to Regulation (EC) No. 1272/2008 [CLP]. ECHA (European Chemicals Agency).
Supplier's safety documents.

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Aquatic Chronic 3	H412

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
H302	Harmful if swallowed.
H312	Harmful in contact with skin.

INTERFLEX EPO AD (B Component)

Safety Data Sheet

according to Regulation (EU) 2015/830

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine). May produce an allergic reaction.

SDS EU (REACH Annex II)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable